

ROTARY FLOOR STANDING DIGITAL SIGNAGE



Panel Parameter

Panel Sizes	43-49-50-55 Inches
Brightness	350cd/m2
Resolution	3840*2160
Contrast Ratio	3000:1
Panel Life	60,000hrs
Responsive Time	<5ms
Viewing Angle	H178/V178

Touch Panel Parameter

Touch Max Resolution	32767 * 32767
Touch Type	Infra-red
Touch point	10 points
Transparency	> 90%, Up to 100%
Scanning Speed	>50Scans/S
Response Speed	<5ms
Communication	USB2.0
Power Supply	DC12V/AC100-240V 50/60Hz

Camera	5MP (optional)	Temperature	Storage:-20°C to 80°C
Applications	Supermarket, Hotel, Mall center, Shop, Commercial buildings etc.	Operating System	Working: -10°C to 65°C
Certificate Approval	CE,RoHS,CCC,FCC,ISO9001	Android system	RK3568 CHIPSET, Quad-core 64-bit
Warranty	Limited One Year Manufacturer Warranty		Cortex-A55, up to 1.8Ghz; GPU: ARM
Features	Set up time on/off Support Remote controller		G52 2EE supports OpenGL ES 1.1/2.0/3.2, OpenCL 2.0, Vulkan 1.1 Android 11.0;
Supported Media Format	Support Safety lock system MPEG1/2/4, AVI, RM, WMV, DAT, JPEG, BMP, PPT, WORD, EXCEL, TXT, MP3, RMVB, SWF etc.		WIFI, Bluetooth 4.2,RJ45 supported RAM:4G Memory: 32G

GUAM

📍 643 Chalan San Antonio, KG Plaza, Suite 107
Tamuning, Guam 96913

✉ info@DimensionSystems.com

☎ Guam: +1 (671) 646-2007 | Saipan: +1 (670) 483-5454

📠 Fax: +1 (671) 646-2006

PHILIPPINES

📍 11F One Corporate Center, Julia Vargas Ave.,
Ortigas Center Pasig City, Philippines 1603

✉ infoph@DimensionSystems.com

☎ +632 8844-0888



SCAN ME